



ICONIC indoor

CABINET
IL SERIES

IL 4 Pro

Indoor fixed ICONIC LED Display are available front & Rear access, super slim design and excellent display performance make it the first choice in subway exit, bus station, HD outdoor media, light pole screen.

Specification

| | |
|--------------------|---------------------------|
| Pixel Pitch | 4mm |
| Pixel Density | 62.500dots/m ² |
| LED Configuration | SMD 2121 |
| Module Size | 320 x 160 (W x H) |
| Module Resolution | 80 x 40 |
| Contrast Ratio | 4.000 : 1 |
| Cabinet Size | 640 x 480mm (W x H) |
| Cabinet Resolution | 160 x 120 |
| Cabinet Weight | Iron : 40kgs |
| Maintenance Type | Front & Rear |
| IP Rating | IP40/31 |

| | |
|---------------------------|-------------------------|
| Brightness | 800nits |
| Viewing Angle | 140°, 140° (H,V) |
| Driving Type | 1/16 |
| Grayscale | 14bit |
| Max/Avg Power Consumption | 750/225W/m ² |
| Voltage | AC 110~240V |
| Frequency | 50/60Hz |
| Refresh Rate | 3.840hz |
| Lifetime | 100.000hours |
| Operating Temperature | -20°C ~ 50°C |
| Operating Humidity | 10% ~ 90% |